Industrial bread line





Heavy-duty bread line. All machines are designed for continual bread processing and are well known for high quality materials, reliable availability and excellent baking results. The line has a capacity of up to 3000 pcs/hour. All machines are produced in Sweden according to CE-regulations.





Industrial bread line with MO-881

SD-300 Suction dough divider



- Stainless steel
- PLC control with touch screen
- Frequency controlled drive
- Very accurate scaling
- Easy to convert between 1-pocket and 2-pocket drive

Options:

- Non-stick coated hopper
- Flour duster
- 59.5 US gal hopper
- Outfeed roller for sticky dough

		SD 300	SD 300 XL
Weight range	1-pocket	3.5 oz - 2.2 lb	8.8 oz - 5.0 lb
Weight range	2-pockets	1.4 oz - 14.1 oz	5.3 oz - 2.5 lb
Capacity	1-pocket	750-1500 pcs/hour	
Capacity	2-pockets	1500-3000 pcs/hour	

CR-310GM Conical rounder



- Centrally adjustable tracks
- Non-stick coated cone and tracks
- Rounding length up to 13 ft
- Patented

Options:

- Frequency converter
- Flour dusterCold/hot air blowing unit
- Outfeed conveyor
- Outfeed roller for sticky dough

Weight range	1.05 oz - 4 lb
Capacity	Up to 3600 pcs/hour

IPP Intermediate pocket proofer



- · Stainless steel
- Non-stick coated transfer box
- Double infeed V-belt conveyor
- Electric control panel
- Central electric cabinet

Options:

- Reversible outfeed conveyor
- Humidification system
- Modular system, up to 940 pockets
- . UV-light

Weight range	3.5 oz - 3.3 lb
Capacity	Up to 3000 pcs/hour

MO-881 Heavy duty moulder





- First class Heavy Duty moulder for all types of bread and baguette production
- Three pair of rollers
- Two pressure boards, the second foldable
- Silent and maintenance free operation


Options:

- Variable speed
- Lower side guides non-stick coated
- Decoration unit
- 4-pieces
- Underlying conveyor for tins
- Depositing system

Weight range	1.05 oz -4 lb
Capacity	Up to 3600 pcs/hour







- 1. SD-300
- 2. CR-310 GM
- 3. IPP
- 4. MO-881



Glimek AB

P.O. Box 124 • S-280 64 GLIMÅKRA • Sweden Phone +46 44 449 00 • Fax +46 44 449 10 e-mail: office@glimek.se • www.glimek.se